

Brooke™



2110FPRO 250w 10"/1" Speaker

Specification

This professional two-way speaker cabinet is purpose-designed to deliver top quality performance and lasting durability in portable, stage and architectural applications. A 10" Bass Driver mounts alongside a symmetrically horned 1" Tweeter for superior high fidelity sound at 250 Watts RMS.

Very flat frequency response offers clear and transparent sound for precision monitoring. Steep crossover slopes minimize floor reflections. Perfect for front-stage and near field applications. Dual angle horn placement for dual purpose main or stage monitor.

The unit can sit vertically on rubber feet, with its integral top-hat on a 35mm pole, or can be used horizontally on the contoured cabinet back. The side and rear have three chassis-bolted aluminium brackets that form secure grab handles for setting up, and carrying and mounting. Black PU crackle-finish covers the cabinet. The front aspect looks superb, with an acoustic foam

backed grille securely fixed into the cabinet.

Speakon-type sockets on the rear of the unit ensure compatibility with standard amplifier connections.

Impedance	8Ω
Power	250 Watts RMS
Frequency	70Hz to 20KHz
Sensitivity	93dB
SPL	93dB, Continuous 119dB
Driver(s)	One 10" Bass with one 1" Tweeter
Input Connection(s)	2 x Speakon® type sockets
Mounting	Floor, 35mm top-hat pole, bracket
Enclosure	Black 18mm Ply
Dimensions	H 480mm x W 320mm x D 320mm
Weight	22kg

Brooke™

brooke-products.com

©2007 Brooke. Errors & Omissions on this User Specification excepted.