

Brooke™



3215XPRO 1400w Twin 15"/2" Speaker

Specification

This professional two-way speaker cabinet is purpose-designed to deliver top quality performance and lasting durability in portable and architectural applications. Twin 15" Bass Drivers mount alongside a symmetrically horned 2" Tweeter for superior high fidelity sound at a massive total of 1400 Watts RMS.

Very flat frequency response offers clear and transparent sound for precision monitoring. Steep crossover slopes minimize floor reflections. Perfect for front-stage and near field applications.

The unit sits vertically on the floor. Each side features three integral grab handles for setting up and carrying. Two non-slip grab handles on each side are designed to for horizontal or vertical lifts - the third is positioned for vertical lift only.

Black PU crackle-finish covers the cabinet and stylish Brooke branding is visible with a prominent logo laser-etched onto the cabinet. The front aspect

Impedance	4Ω
Power	1400 Watts RMS
Frequency	40Hz to 18KHz
Sensitivity	104dB
SPL	104dB
Driver(s)	Two 15" Bass with one 2" Tweeter
Input Connection(s)	2 x Speakon® type sockets
Mounting	Floor
Enclosure	Black 18mm Ply
Dimensions	H 1140mm x W 465mm x D 460mm
Weight	77kg

looks superb, with an acoustic foam covered grille that is removed with a recessed notch at the top of the cabinet. The grille is secure by magnetic clamps and a hidden retaining wire prevents total removal or loss of the grille.

Speakon-type sockets on the rear of the unit ensure compatibility with standard amplifier connections.

Brooke™

brooke-products.com

©2007 Brooke. Errors & Omissions on this User Specification excepted.